

MACCOR

High Volume Cycles



*192 position
model 4600*

The multifunction series 4600's (Models 4600 and 4650) secondary cell test systems have been engineered to provide high capabilities for large scale single cell testing. Each test position:

- Operates independently of the other positions
- Can be user programmed to run a wide range of multi step tests,
- Can be user programmed to operate in steps of constant current, constant power, constant voltage, or constant resistance
- Is delivered calibrated to NIST traceable standards, and requires calibration only once per year

The Series 4600 is supplied as a complete turnkey system with PC computer and software. Each system is available from a 32 position desktop model to large test and quality control models with thousands of test positions. Desktop models are usually available from stock.

Powered by Maccor's standard battery testing software and utilizing the same technology found in Maccor's high precision Series 4000 laboratory test systems, the Series 4600's are ideal for today's testing standards. During the test, data is recorded at operator specified intervals. At any time during the test data can be viewed or plotted. The software can be configured to automatically add key test data to Maccor's MIMS database. Additionally, custom data handling interfaces or user interfaces can be purchased.

The Model 4600 has a Phoenix connector interface with horizontal cell configuration providing a dense and compact configuration. Each cabinet (standard 19" rack) can have up to 192 test positions. The Model 4600 is also available in a desktop cabinet with 32-test positions.

The Model 4650 has a Powerpole® interface with vertical cell configuration. The 4650 has a slightly larger footprint than the 4600, each cabinet can be configured with as many as 256 test positions.

For production and quality control systems, test positions can be accessed remotely with a PC over a wireless network interface allowing the operator to view, start, and stop tests directly at the cell interface. For more information contact Maccor's Sales Department.

Specifications

Current Range	2500 mA Full Scale ± 2.5 mA
Voltage	
Measurement Range	0 – 5 volts ± 5 mV
Minimum Discharge	0.35 x Current
Modes of Operation	
Constant Current	
Constant Power	
Constant Resistance	
Constant Voltage	
Time	
Minimum Step Time	500 mS
Control, Measurement, and Adjustment	every 50 mS

Options

Cell Holders	
Molded True 4-Wire Kelvin Cell Holders	AAA, AA, C, and D
Universal button cell holders	
Spring Loaded Binding Posts	
Cables	
Contact Maccor's Sales Department for Length and Terminations	
Uninterruptable Power Supply	
Calibration and Maintenance Service	



32 Position Desktop Model 4600 desktop

MACCOR

Maccor, Inc

2805 West 40th Street Tulsa, Oklahoma 74107 USA
Telephone: 918 446-1874 Facsimile: 918 445-1496
Web: www.maccor.com e-mail: sales@maccor.com